



# TensorGrip®

# CALIFORNIA THREE FOR ALL

## OVERVIEW

TensorGrip® is a brand with a purpose. And that purpose is making your job easier.

Begin with three of our outstanding products. Designed specifically for the major tasks of the woodworking and laminate market, you'll have the products and the power to succeed.

## SIMPLE LABELING

With TensorGrip®, you won't need to read the fine print on labels again. At a glance, any person — no matter what the language or literacy — will be able to identify the product and what it's for.

Relax. And prepare to outperform!

Distributed by:

[www.quinglobal.com](http://www.quinglobal.com)  
[www.tensorglobal.com](http://www.tensorglobal.com)  
[sales.us@quin-global.com](mailto:sales.us@quin-global.com)  
+1 402 731 3636

QUIN  
GLOBAL  
**Tensor**<sup>TM</sup>



# CALIFORNIA THREE FOR ALL



**Tensorgrip**<sup>®</sup>  
Adhesives That Outperform



3 FOR ALL

L20

LOW VOC  
SPRAY CONTACT ADHESIVE

**Your trusty companion.**

TensorGrip® L20 is your work horse, working long and hard to please you whenever you're doing standard laminate and general bonding. The finished product will be excellent, built to last. Not only that, but also it complies with the strict air quality regulations of SCAQMD. Formulated with unique CO-REZ™ Technology, L20 is sure to please!



Standard  
Laminate



# L15

## THE ULTIMATE AGGRESSIVE CONTACT ADHESIVE

Call it tough. TensorGrip® L15 is made for the job. Designed to instantly grab a permanent hold even in situations where there's a lot of tension on the adhesive. L15 does its best work on curved surfaces (bender board/flexible plywood) and the wood buildups used under solid surface counter tops. Plus, it's SCAQMD approved!



### DIRECTIONS FOR USE

Product Data and Health and Safety Data Sheets (MSDS) must be read and understood before use. ALWAYS test to determine suitability for your particular application before use in production. Substrates to be bonded must be clean, dry and free of contaminants. Correct coat weight of adhesive must be applied. Substrates may be painted. See Product Data Sheet and Health and Safety Data Sheet for more information. NOT RECOMMENDED for use with EPS (EPS).

dry for 1-2 mins.  
g time in humid or cold  
state even pressure.

Part # PH1 385  
Tel: 0045 381 22 33 | www.springlobal.com



Bender  
Board



Wood  
Buildups






# L64

## ULTRA LOW PROFILE CONTACT ADHESIVE

**Absolutely flawless.** When your client asks for shiny, beautiful laminate; they don't want something that has that rippled, bumpy look. TensorGrip® L64 shines in flat applications and keeping your best work looking great. Postformable? Check. Got you covered. And still SCAQMD compliant.



### SIGNAL WORD

Danger

### HAZARD STATEMENTS

H222 Extremely flammable liquid or solid  
H229 Pressurized container  
H301 Dangerous for humans

### PRECAUTIONARY STATEMENTS

P201 Obtain special advice before use  
P202 Do not handle until instructed  
P210 Keep away from heat, open flames, other ignition sources  
P211 Do not spray  
P251 Do not pierce or crush  
P280 Wear protective gloves/eye protection/face protection if exposed  
P308+P313 If exposed or concerned: Get medical attention immediately  
P405 Store locked  
P410+P412 Protect from sunlight  
P501 Dispose of contents and container in accordance with local, state, and federal regulations.

### CONTAINS

DICHLOROMETHANE



Postforming



High Gloss/  
Definition Laminate

Thin  
Veneers

