



# TensorGrip®

# CANISTER SYSTEM

## OVERVIEW

TensorGrip® is a brand with a purpose. And that purpose is making your job easier.

Begin with three of our outstanding products. Designed specifically for the major tasks of the woodworking and laminate market, you'll have the products and the power to succeed.

## SIMPLE LABELING

With TensorGrip®, you won't need to read the fine print on labels again. At a glance, any person — no matter what the language or literacy — will be able to identify the product and what it's for.

Relax. And prepare to outperform!

Distributed by:

[www.quinglobal.com](http://www.quinglobal.com)  
[www.tensorglobal.com](http://www.tensorglobal.com)  
[sales.us@quin-global.com](mailto:sales.us@quin-global.com)  
+1 402 731 3636

QUIN  
GLOBAL  
**Tensor™**



# CANISTER SYSTEM

CLEANER. FASTER.  
**SMARTER.**



**Tensorgrip®**  
Adhesives That Outperform



# CANISTER SYSTEM

## CLEANER

Your long-standing love-hate relationship with pressure pots, brushes, rollers and sprayers is over.

TensorGrip® canisters are designed to eliminate the mess of traditional glue application methods.

- No equipment cleanup
- Less wasted material
- Minimal glue spillage



# FASTER

Not one moment wasted. Get more out of your daily grind.

When you're setting up to use TensorGrip® canisters, just attach the gun and hose, and you're set to spray.

No cleanup, no setup, no worries.

Plus, choose from a range of sizes to get a system that suits your application best.



Aerosols (650ml), Large (22L), Intermediate (108L), Jumbo (216L)

Product Data Sheet (PDS) and Safety Data Sheets (MSDS) must be read and understood before use. ALWAYS test to determine suitability for your particular application before use in production. Substrates to be bonded must be clean and free of dust, dirt, grease etc. Correct coat weight of adhesive must be applied - see Product Data Sheet and User Manual. Double coat of adhesive is recommended around perimeters and may be necessary on porous or difficult substrates - see Product Data Sheet and User Manual. Apply ADEQUATE PRESSURE to ensure solid bond - see Product Data Sheet and User Manual. NOT RECOMMENDED for use with substrates: PP, PE, polystyrene (EPS).

#### PERMANENT BONDING

Spray both surfaces in the opposite direction. Allow to dry for 1-2 mins before placing substrates together. (Allow more drying time in humid or cold climates). Re-alignment is not possible. Apply adequate even pressure.

Qing Global Ltd  
10000 Field Avenue  
Industrial Estate  
www.qinglobal.com  
Tel: 0845 381 22...  
www.qinglobal.com





# SMARTER

1 = 3. Yes, our math is right. One large canister will get you the equivalent coverage of three pails of traditional contact adhesive – when applied at recommended coverage.

Plus:

- Efficient spray – no wasted glue
- Consistent coverage & pattern
- Easy to identify product uses
- Designed with the user in mind – fun to use, effective and reliable

#### SIGNAL WORD

Danger

#### HAZARD STATEMENTS

H222 Extremely flammable liquid and vapour  
 H281 Corrosive to metals

#### PRECAUTIONARY STATEMENTS

P201 Obtain special advice before use  
 P202 Do not handle if you do not have special information  
 P210 Keep away from heat, open flames, other ignition sources  
 P211 Do not spray towards yourself or others  
 P251 Do not permit children to have access to this product  
 P280 Wear protective gloves/protective clothing/eye protection/face protection  
 P308+P313 IF exposed or concerned: Get medical advice/first aid immediately  
 P405 Store locked up  
 P410+P412 Protect from sunlight  
 P501 Dispose of contents and container in accordance with local, national, and international regulations.

#### CONTAINS

DICHLOROMETHANE

L12 THE ULTIMATE WATER-BASED CONTACT ADHESIVE

Tensorgrip

SIZE: 22LTR  
COLOUR: CLEAR

UN3501  
CHEMICAL UNDER PRESSURE, FLAMMABLE,  
N.O.S. (DIBROMOMETHANE CLASS 2.1)

