



SAFETY DATA SHEET

Tensorgrip F50AA Low VOC Contact Adhesive

1. Identification

Product identifier

Product name Tensorgrip F50AA Low VOC Contact Adhesive
Product number USA

Recommended use of the chemical and restrictions on use

Application Aerosol Spray Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global
 5710 F St
 (402) 731 3636
 (402) 731 1473
 marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification


Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280
Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards Aquatic Chronic 3 - H412

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H302+H332 Harmful if swallowed or if inhaled.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361f Suspected of damaging fertility.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Tensorgrip F50AA Low VOC Contact Adhesive

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplemental label information

AT(o) 18.0% of the mixture consists of ingredient(s) of unknown acute oral toxicity.

Contains

Methyl Acetate, Propane, Isobutane, n-Hexane

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Substances

Mixtures

Methyl Acetate 30-60% CAS number: 79-20-9
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336
Propane 10-30% CAS number: 74-98-6
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280 Acute Tox. 4 - H332 Simple Asphyxiant - USH03
Isobutane 10-30% CAS number: 75-28-5
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280

Tensorgrip F50AA Low VOC Contact Adhesive

n-Hexane 5-10% CAS number: 110-54-3 M factor (Acute) = 1
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Aquatic Chronic 2 - H411

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Remove contaminated clothing. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

General information	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
Ingestion	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.

Tensorgrip F50AA Low VOC Contact Adhesive

Eye contact

Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. No smoking, sparks, flames or other sources of ignition near spillage. Avoid the spillage or runoff entering drains, sewers or watercourses. Eliminate all sources of ignition. Wash thoroughly after dealing with a spillage. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

Specific end uses(s)

Tensorgrip F50AA Low VOC Contact Adhesive

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Methyl Acetate

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m³

Propane

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 1800 mg/m³ 1000 ppm

Long-term exposure limit (8-hour TWA): OSHA 1800 ppm 1000 mg/m³

Isobutane

Long-term exposure limit (8-hour TWA): ACGIH 1000 ppm

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 800 ppm 1900 mg/m³

n-Hexane

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

Sk

Ceiling Value: OSHA_TRANS 500 ppm 1800 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 50 ppm 180 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

Sk = Danger of cutaneous absorption.

Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Wash promptly with soap and water if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

9. Physical and Chemical Properties

Tensorgrip F50AA Low VOC Contact Adhesive

Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Clear. Red.
Odor	Organic solvents.
Initial boiling point and range	-42.1°C (-43.8°F)
Flash point	-104°C/-155°F CC (Closed cup).
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 9.5 g/100 g Lower flammable/explosive limit: 2.1 g/100 g
Relative density	~ .928
Solubility(ies)	Negligibly soluble in water
Volatile organic compound	This product contains a maximum VOC content of 249.2176 g/l.

10. Stability and reactivity

Stability	Stable at normal ambient temperatures and when used as recommended.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Reducing agents. Avoid contact with the following materials: Oxidizing agents.
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Aldehydes. Halogenated hydrocarbons.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 975.08

Acute toxicity - dermal

ATE dermal (mg/kg) 2,616.06

Acute toxicity - inhalation

ATE inhalation (gases ppm) 25,000.0

ATE inhalation (vapours mg/l) 18.32

Toxicological information on ingredients.

Methyl Acetate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

Tensorgrip F50AA Low VOC Contact Adhesive

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 49.28

Species Rat

ATE inhalation (vapours mg/l) 11.0

Propane

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 1,442.0

Species Rat

Acute toxicity inhalation (LC₅₀ vapours mg/l) 1,442.0

Species Rat

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

Isobutane

Toxicological effects No information available.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Inhalation Suffocation (asphyxiant) hazard

Skin Contact Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Eye contact Spray will evaporate and cool quickly and may cause frostbite or cold burns if in contact with skin.

n-Hexane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 25,000.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Tensorgrip F50AA Low VOC Contact Adhesive

Species	Rabbit
ATE dermal (mg/kg)	1,100.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	171.6
Species	Rat
ATE inhalation (vapours mg/l)	11.0
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Suspected of damaging fertility.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause drowsiness or dizziness
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Target organs	Central nervous system
<u>Aspiration hazard</u>	
Aspiration hazard	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<u>General information</u>	
	After absorption. Tiredness. Narcosis. After long term exposure to the chemical: CNS disorders, paralysis symptoms. (It generally applies to aliphatic hydrocarbons with 6 - 18 carbon atoms that they cause pneumonia, in some cases also pulmonary edema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar.)) Absorption of large quantities may cause: Narcosis. Possible risk of adverse reproductive effects.
Inhalation	May cause drowsiness or dizziness. Vapors irritate the respiratory system.
Ingestion	Irritating. May cause nausea, stomach pain and vomiting.
Skin Contact	The product is irritating to eyes and skin.
Eye contact	Risk of corneal clouding.
Route of entry	Inhalation Skin and/or eye contact
Target Organs	Eyes Skin Respiratory system, lungs Central nervous system Peripheral nervous system

12. Ecological Information

13. Disposal considerations

Waste treatment methods

Tensorgrip F50AA Low VOC Contact Adhesive

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

Air transport notes 1. <75kg, 2. <150kg

UN Number

UN No. (DOT) Limited Quantity <1L, Aerosol

UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name (DOT) Aerosols, Flammable (Methyl Acetate, Hexane)

Transport hazard class(es)

DOT hazard class 2.1

Transport labels



Packing group

Not applicable.

15. Regulatory information

US Federal Regulations

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

n-Hexane

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

n-Hexane

100%

SARA (311/312) Hazard Categories

Hazard

Propane

Yes.

Isobutane

Fire
Pressure
Hazard

Methyl Acetate

Fire
Acute
Chronic
Health hazard

Tensorgrip F50AA Low VOC Contact Adhesive

n-Hexane

Acute
Chronic
Health hazard
Fire

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Propane

Present

Isobutane

Present

Methyl Acetate

Present

n-Hexane

Present

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Propane

Present.

Isobutane

Present.

Methyl Acetate

Present.

n-Hexane

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Propane

Present.

Isobutane

Present.

Methyl Acetate

Present.

n-Hexane

Present.

Inventories

Canada - DSL/NDSL

The following ingredients are listed or exempt:

Tensorgrip F50AA Low VOC Contact Adhesive

Propane

DSL
Present.

Methyl Acetate

All the ingredients are listed or exempt.

n-Hexane

DSL

US - TSCA

Present.

Propane

Present.

Methyl Acetate

Present.

n-Hexane

Present.

16. Other information

Revision date	2/17/2016
Revision	3
Supersedes date	3/9/2015
SDS No.	20425
Hazard statements in full	<p>USH03 May displace oxygen and cause rapid suffocation</p> <p>H220 Extremely flammable gas.</p> <p>H222 Extremely flammable aerosol.</p> <p>H225 Highly flammable liquid and vapor.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H302 Harmful if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H361f Suspected of damaging fertility.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
ACA HMIS Health rating.	Slight hazard. (1)
ACA HMIS Flammability rating.	Extremely flammable. (4)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	B

Tensorgrip F50AA Low VOC Contact Adhesive

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application