

Tensorgrip

SAFETY DATA SHEET

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

1. Identification

Product identifier

Product name Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

Recommended use of the chemical and restrictions on use

Application Canister Spray Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global
5710 F St
(402) 731 3636
(402) 731 1473
marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards

Aerosol 2 - H223, H229 Press. Gas, Compressed - H280

Health hazards

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336

Environmental hazards

Aquatic Chronic 2 - H411

Human health

The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram



Signal word

Warning

Hazard statements

H223 Flammable aerosol.
H229 Pressurized container: may burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

- P264 Wash contaminated skin thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.

Contains Methyl Acetate, Heptane

Other hazards

This product does not contain any substances classified as PBT or vPvB.

Other hazards

3. Composition/information on ingredients

Substances

Mixture Statement

Mixtures

Methyl Acetate	60-100%
CAS number: 79-20-9 REACH registration number: 01-2119459211-47-XXXX	

Classification
Flam. Liq. 2 - H225
Acute Tox. 4 - H302
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Eye Irrit. 2A - H319
STOT SE 3 - H336

Heptane	1-5%
CAS number: 142-82-5 REACH registration number: 01-2119457603-38-XXXX	
M factor (Acute) = 1 M factor (Chronic) = 1	

Classification
Flam. Liq. 2 - H225
Acute Tox. 4 - H302
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
STOT SE 3 - H336
Asp. Tox. 1 - H304
Aquatic Acute 1 - H400
Aquatic Chronic 1 - H410

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information

Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.

Inhalation

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.

Ingestion

Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact

Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

Inhalation

May cause respiratory irritation. Exposure may cause coughing or wheezing. Headache. Sore throat. Irritation of nose, throat and airway. Overexposure may depress the central nervous system, causing dizziness and intoxication.

Ingestion

Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhea. Prolonged or repeated exposure may cause the following adverse effects: Central nervous system depression.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Symptoms following overexposure may include the following: Irritation and redness, followed by blurred vision.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards

Pressurized container: Must not be exposed to temperatures above 50°C/120°F. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Advice for firefighters

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

Environmental precautions

Environmental precautions

Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions

Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Methyl Acetate

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm
Short-term exposure limit (15-minute): ACGIH 250 ppm
Long-term exposure limit (8-hour TWA): OSHA 200 ppm 610 mg/m³

Heptane

Long-term exposure limit (8-hour TWA): ACGIH 400 ppm
Short-term exposure limit (15-minute): ACGIH 500 ppm
Long-term exposure limit (8-hour TWA): OSHA 500 ppm 2000 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.
OSHA = Occupational Safety and Health Administration.

Methyl Acetate (CAS: 79-20-9)

Immediate danger to life and health
3100 ppm

Heptane (CAS: 142-82-5)

Immediate danger to life and health
750 ppm

Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists.

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Aerosol.

Color

Clear. Red.

Odor

Solvent.

Initial boiling point and range

-44°F @ 1013.25 mbar -42°C @ 1013.25 mbar

Flash point

~ -156°F Not specified. ~ -104°C Not specified.

Upper/lower flammability or explosive limits

Lower flammable/explosive limit: 1.8 g/100 g Upper flammable/explosive limit: 18 g/100 g

Relative density

~ .946

Solubility(ies)

Negligibly soluble in water

Volatile organic compound

This product contains a maximum VOC content of 38 g/l.

10. Stability and reactivity

Stability

Stable at normal ambient temperatures and when used as recommended.

Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.

Materials to avoid

Flames and Sparks

Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Aldehydes. Hydrocarbons.

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive**11. Toxicological information****Information on toxicological effects****Acute toxicity - oral****ATE oral (mg/kg)**

686.7188573

Acute toxicity - dermal**ATE dermal (mg/kg)**

1510.78148606

Acute toxicity - inhalation**ATE inhalation (vapours mg/l)**

15.10781486

Toxicological information on ingredients.**Methyl Acetate****Acute toxicity - oral****Acute toxicity oral (LD₅₀ mg/kg)**

5,000.0

Species

Rat

ATE oral (mg/kg)

500.0

Acute toxicity - dermal**Acute toxicity dermal (LD₅₀ mg/kg)**

2000.0

Species

Rat

ATE dermal (mg/kg)

1100

Acute toxicity - inhalation**Acute toxicity inhalation (LC₅₀ vapours mg/l)**

49.28

Species

Rat

ATE inhalation (vapours mg/l)

11.0

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

Heptane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)

5,000.0

Species

Rat

ATE oral (mg/kg)

500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg)

2000.0

Species

Rabbit

ATE dermal (mg/kg)

1100

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)

29.3

Species

Rat

ATE inhalation (vapours mg/l)

11.0

Carcinogenicity

Does not contain any substances known to be carcinogenic.

Specific target organ toxicity - single exposure

STOT - single exposure

May cause drowsiness or dizziness

General information

Absorption of large quantities may cause: Narcosis. Death.

12. Ecological Information

13. Disposal considerations

Waste treatment methods

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

Air transport notes Cargo aircraft only. 75kg

UN Number

UN No. (DOT) 3501

UN No. (ICAO) 3501

UN proper shipping name

Proper shipping name (DOT) 3501 - Chemical Under Pressure, Flammable, N.O.S. (Methyl Acetate, Heptane)

Transport hazard class(es)

DOT hazard class 2.1

Tensorgrip P313 Low VOC Pebble Spray Contact Adhesive

Transport labels



Packing group

Not applicable.

15. Regulatory information

Inventories

US - TSCA

Present

16. Other information

Revision date 8/11/2014

Revision 4

Supersedes date 8/11/2014

SDS No. 20360

Hazard statements in full

H223 Flammable aerosol.

H229 Pressurized container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

ACA HMIS Health rating. Moderate hazard. (2)

ACA HMIS Physical hazard rating. Normally stable. (0)

ACA HMIS Personal protection rating. B

ACA HMIS Flammability rating. Ignites easily. (3)

Disclaimer

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application