

TensorGrip®

L22

NON-MECL FINE WEB
SPRAY ADHESIVE

SUITABLE FOR:



Aluminium Sheeting



Standard Laminate

PROPERTIES:



Web Spray



California Compliant

AVAILABLE IN:



500ml Aerosol



22ltr Canister

COLOURS:



Clear



Red

TECHDATA

PRODUCT DESCRIPTION

TensorGrip® L22 is a fine spray adhesive for permanent bonding of materials where immediate bond strength, water resistance and high heat resistance are required. It is suitable for bonding HPL, hard plastics, GRP, foams and fabrics to a variety of substrates including MDF, chipboard, plywood and many other timber sheet materials. The L22 can also be used for bonding sheet metals where surface preparation is very important.

ADVANTAGES

- Fast Drying.
- Good Heat Resistance.
- Very High Solids.
- Non-Chlorinated Adhesive.

DIRECTIONS FOR USE

- This product is designed to be applied to two surfaces to be bonded together. Make sure that surfaces are clean, dry and free from dirt, dust, oil, loose paint, wax or grease, etc. For best results, the temperature of the adhesive and the surfaces being bonded should be between 60 °F - 80 °F (16 °C - 27 °C).
- We recommend shaking the aerosol can well before using.
- Prior to use, Check compatibility by spraying a small test patch of the adhesive on the substrate. This product may degrade some substrates. Spray about 5 - 10 cm (2" - 4") away at a 90° angle to the surface, applying a uniform, even coat of adhesive to obtain 80% to 100% coverage of the surface. If necessary, spray another coat of adhesive in areas that appear to need more adhesive. Spray both surfaces to be bonded, one surface vertically and the other surface horizontally. Allow the adhesive to tack off until no adhesive transfers to the knuckle when touched.
- Adhere surfaces and press together with adequate pressure. A roller or a mallet is recommended to apply a uniform pressure to achieve maximum strength. Allow 24 hours for the adhesive to fully cure.

SPECIAL PRECAUTIONS

- For optimum results store canister above 18°C during use, but must always be above 10°C. Allow substrates to acclimatise to normal room temperature (18°C) for 48 hours before bonding. Do not exceed open time of the adhesive. Keep canister off cold concrete floors during use. If adhesive is expelled wet or as a jet, aerosol is too cold – move to warm environment and allow to thoroughly acclimatise before reusing.
 - MSDS and Technical Data Sheets MUST be read and understood before use. Information contained in this technical literature is believed to be accurate and offered in good faith for the benefit of the consumer. The company however cannot assume any liability or risk involved in the use of its chemical products since the conditions of use are beyond our control. Statements concerning the possible use of our products are not intended as recommendations to infringe on any patent.
- CAUTION**
- Use only in well ventilated areas.
 - DO NOT thin or reactivate with solvents.
 - DO NOT incinerate.
 - DO NOT expose to extreme heat > 50°C.
 - Keep away from sources of ignition.
 - Test for suitability before use.

Tensorgrip®

L22

NON-MECL FINE WEB
SPRAY ADHESIVE



CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

Total Solids	34%
Colour	Clear or Red
System Flammability	Flammable adhesive in flammable propellant
Shear	> 250 p.s.i.
Tensile (180° Peel)	> 25 p.l.i.
90° Peel (6.25 sq.cm)	> 25 p.s.i.
Shear adhesion failure temp. (SAFT) 100gram	> 115°C
Dry time	3-5 mins dependant on temp & humidity
Open time	50 mins
SHELF LIFE	18 months from date of manufacture

PACKAGING

500ml	Aerosol suitable for industrial and general public use
22ltr	Disposable Canister (suitable for industrial use only)

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- DO NOT store at temperatures over 50°C.
- Avoid exposure to direct sunlight.
- DO NOT store directly on concrete floor.
- For optimum performance, store at 18°C during use, but must always be above 10°C.
- Always test product to determine suitability for your particular application prior to use in production.

Copyright © 2018 by Quin Global UK Ltd All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

QUIN
GLOBAL

QUIN GLOBAL UK
Unit 1 Ruthvenfield Avenue,
Inveralmond Industrial
Estate, Perth, PH1 3WB

T: +44 (0) 845 381 2233
E: info.uk@quinglobal.com
www.quinglobal.com

Tensorgrip®

