

# Tensorgrip®

# H21

2 PART EXPANDING  
FOAM KIT

## IMPORTANT

Check temperatures  
before use!

## CANISTER TEMPERATURE

16° – 32°C

## SURFACE TEMPERATURE

16° – 32°C

## AIR TEMPERATURE

16° – 32°C

# TECHDATA

## PRODUCT DESCRIPTION

TensorGrip® H21 2 Part Expanding Foam Kit is a professional-grade, portable multipurpose expanding sealant. The H21 is a 2-part PU component foam that is suitable for use in Hard Rock mining and construction repairs. It serves as an airtight sealant, effectively insulating, filling, and sealing gaps and voids and can be used for various purposes such as sealing around ventilation structures, sealing cable bolt holes prior to grouting, small cavity filling, and containment barriers in underground mining. Additionally, it is suitable for the insulation industry, including renovations, new insulations, movie props, and special effects applications. This high-quality product is manufactured in Australia and boasts a closed cell structure of over 92%.

## SUITABLE FOR

- Commercial buildings
- Residential properties
- Hard rock mining
- Movie props
- Shipping containers
- Vans and camper vans
- Metal frame house builds
- Industrial maintenance

## DIRECTIONS FOR USE

IMPORTANT – READ ALL DIRECTIONS AND SAFETY DATA ON BOX BEFORE USE. ALWAYS WEAR GLOVES, EYE PROTECTION AND WORK CLOTHES. USE DROP CLOTHS.

- Apply ONLY in temperatures between 16° – 32°C.

**PREPARATION:** To promote adhesion, surface must be clean, dry, and free of all foreign material.

All substrate surfaces should be above 16°C for at least 24 hours prior to application. Variance outside of the recommended temperature can drastically affect the adhesion and yield of your foam kit.

**CLEAN-UP:** If wet foam contacts skin, clean immediately with a dry rag – do not use water – water accelerates curing. Cured foam must be removed mechanically from surfaces. Uncured foam can be cleaned from most surfaces with Foam Cleaner or acetone.

If foam dries on skin, apply generous amounts of petroleum jelly, put on plastic gloves and wait 1 hour. With a clean cloth, firmly wipe off residue and repeat process if necessary. DO NOT use acetone or other solvents to remove product from skin.

**STORAGE & DISPOSAL:** Keep container tightly closed in a cool, well-ventilated area. Store upright below 33°C. Do not expose containers to conditions that may damage, puncture, or burst the containers.

Dispose of leftover material / containers in accordance with national regulations.

Know how to set-up your canisters by scanning on the QR Code



# Tensorgrip®

# H2I

2 PART EXPANDING  
FOAM KIT

## CHEMICAL TECHNICAL DATA

Yield	7 Litre approx. 17.7m <sup>2</sup> @ 25mm Cubic Yield* is 0.4425m <sup>3</sup>  22 Litre approx. 56.64m <sup>2</sup> @ 25mm Cubic Yield* is 1.416 m <sup>3</sup> <i>*based on theoretically testing.</i>
Dry Time	120 seconds @25°C
Cure Time	approx. 1 hour
Application Temperature Range	It is very important to apply in temperatures between 16 °C – 32 °C
Cutttable	2 – 5 minutes
ASTM D1622 Core Density	28.0kg/m3 +/- 2.0 kg/m3
ASTM D6226 Closed Cell Content	+ 92%
ASTM C518-2021 Thermal Conductivity 50/90 mm	0.037 w/m.k
ASTM C518-2021 R value	50mm R1.35 90mm R2.45
ASTM D1621 Compressive strength	75 kpa
ASTM D2126 Dimensional stability, %Vol	-0.2 @ 20°C +3.1 @ 70°C
ASTM E96 water vapour transmission	2.48g/hr.m2
Shelf Life	12 Months from date of manufacture
<b>AS/NZS 1530.3-1999 Early Fire Hazard</b>	
Regulatory Indices: Ignitability Index Spread of Flame Index Heat Evolved Index Smoke Developed Index	18 Range 0 - 20 8 Range 0 - 10 5 Range 0 - 10 7 Range 0 - 10

Copyright © 2022 by Quin Global AU Ltd All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.



Quin Global AU  
PO Box 6196  
Queanbeyan NSW 2620

1300 857 846  
[www.quinglobal.com.au](http://www.quinglobal.com.au)  
[sales@quinglobal.com.au](mailto:sales@quinglobal.com.au)