




Tensorgrip® G67 Aerosol Can is a water based pressure sensitive flooring adhesive designed for small jobs or repairs.



Carpet Tile



LVT/LVP/VCT



Underlayment



Snowflake Spray



California  
Compliant



CO-REZ  
Technology



ZERO-FLAM  
TECHNOLOGY

## PRODUCT DESCRIPTION

Tensorgrip G67 Aerosol Can is a water based pressure sensitive flooring adhesive, suited for small jobs and repair jobs. Tensorgrip G67 is formulated for bonding carpet tile, LVT/LVP/VCT and underlayment and allows for material to be laid into wet adhesive and a releasable bond when dried. Formulated with CO-REZ Technology, which is an exceptional formulation incorporating a highly engineered resin and gas matrix. The result: Greater Coverage from Less Aerosol Weight. Incorporating the unique and innovative No-Slip ProTip nozzle design eliminating annoying and costly nozzle slip offs.

### THIS UNIQUE PORTABLE, FULLY CONTAINED AEROSOL IMPROVES:

**Ergonomics**—Allowing you to stand while applying the adhesives, reducing stress on the back, knees, and shoulders.

**Profitability**—Decreases adhesive times by as much as 70% as compared to troweled or rolled-on adhesives.

**Efficiency**—Allows you to install flooring substrate immediately after spraying G67, rather than waiting hours for troweled or rolled-on adhesives to dry. Ready for Traffic Immediately.

## ADVANTAGES

- CO-REZ Formula. Higher Coverage from Less Aerosol Weight
- Excellent Adhesion to most carpet tiles and LVT/LVP/VCT. Plasticizer Resistant
- No-Slip ProTip eliminates nozzle slip-offs
- Designed for Small Jobs / Repair Jobs. For Large Areas, use G67 Canisters
- Extreme High Coverage 160 - 200 sq ft.
- High Application Speed
- Repositionable during installation.
- Releasable bond for ease of flooring replacement
- No Flammable Ingredients
- Can be wet laid when at least one surface is porous, such as wood or concrete
- Zero VOC, California SCAQMD Rule 1168 Compliant

## PREPARATION & APPLICATION

Suitable subfloors include self-levelling compounds, plywood (underlayment grade), OSB, hardboard and existing non-cushion backed resilient floors (must be well bonded, sound, smooth and free of all waxes, finishes, strippers and cleaners). All paint varnish, oil, wax and any other finishes which may inhibit good bond should be removed. Repair all joints and cracks with a latex based levelling compound. Subfloors should be subject to 28 days of maturing and should have a maximum of 10.8% moisture content before using this adhesive. Do not use this adhesive above these recommendations.

Subfloor preparation and moisture and PH testing must comply with industry standards, and floor-covering manufacturer's guidelines. The floor, room temperature, and the flooring materials must be maintained in accordance with floor covering manufacturer's recommendations

All subfloors should be free of dust prior to application.

## DIRECTIONS FOR USE

Tensorgrip G67 is designed as a portable, self-contained aerosol can for small jobs or repair jobs.

- Shake aerosol can well before use.
- Hold the aerosol can upside down approx. 24" to 36" from the floor at an approximate 30 degree angle.
- Apply adhesive to the floor at 80% to 90% coverage. Do not let adhesive puddle.
- Clean adhesive off the nozzle with water to avoid poor spray pattern.
- Apply slight sideways/upward pressure to the nozzle to spray adhesive.
- Allow enough time (10-15 minutes or until translucent) for the adhesive to become tacky before bonding.

## CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES	
VOC Content	0 % per weight
Flammability	Non-flammable propellant and water-based
Dry Time	10-15 minutes dependant on temp & humidity
Open Time	4+ hours depending on atmospheric conditions
PH Rating	13.2
RH Rating	99.5%
Moisture %	10.8%
Shelf Life	12 months
Coverage	160-200 square feet

PACKAGING	
650 ML (22 FL OZ)	Aerosol Can

## HANDLING AND STORAGE

- Consult Safety Data Sheet prior to use.
- Store at temperatures between 60°F/15°C and 120°F/50°C.
- KEEP FROM FREEZING. Freezing will render this product unusable.
- Avoid exposure to direct sunlight.
- Do not store directly on the concrete floor.
- Aerosol can will spray adequately above 60°F.
- In the event the aerosol can is abnormally chilled or sprays poorly, it should be warmed up before continued use. Warm aerosol by immersion in warm water is suggested.
- Always test product to determine suitability for your particular application prior to use in production.

**DISCLAIMER OF WARRANTY:** Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.



## SAFETY DATA SHEET

### Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

#### 1. Identification

##### Product identifier

**Product name** Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

**Product number** USA

##### Recommended use of the chemical and restrictions on use

**Application** Aerosol Spray Adhesive

##### Details of the supplier of the safety data sheet

**Supplier** Quin Global US, Inc.  
5710 F St  
Omaha NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

##### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Aerosol 3 Press. Gas, Compressed - H280

**Health hazards** Not Classified

**Environmental hazards** Not Classified

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

##### Label elements

##### Hazard symbols



**Signal word** Warning

**Hazard statements** H280 Contains gas under pressure; may explode if heated.

**Precautionary statements** P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 If exposed or concerned: Get medical advice/ attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.

# Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

## Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

### Mixtures

HFO-1234ze, trans-1,3,3,3-Tetrafluoroprop-1-ene	30-60%
CAS number: 29118-24-9	
<b>Classification</b>	
Press. Gas, Liquefied - H280	

The full text for all hazard statements is displayed in Section 16.

## 4. First-aid measures

### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
<b>Ingestion</b>	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

## 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

**Specific hazards** Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

## 8. Exposure controls/Personal protection

### Control parameters

#### Occupational exposure limits

#### HFO-1234ze, trans-1,3,3,3-Tetrafluoroprop-1-ene

TWA of 800 ppm WEEL:US OARS. WEELs Workplace Environmental Exposure Level Guide

## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

### HFO-1234ze, trans-1,3,3,3-Tetrafluoroprop-1-ene (CAS: 29118-24-9)

**Ingredient comments** No exposure limits known for ingredient(s).

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

##### Eye/face protection

Wear chemical splash goggles.

##### Hand protection

Use protective gloves.

##### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

##### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

##### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Color</b>	White/Milky
<b>Odor</b>	Sweetish.
<b>Relative density</b>	1.0-1.04
<b>Solubility(ies)</b>	Soluble in water.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 0.0% by weight .

## 10. Stability and reactivity

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Aldehydes. Halogenated hydrocarbons.

## 11. Toxicological information

## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

### Information on toxicological effects

#### Toxicological information on ingredients.

#### HFO-1234ze, trans-1,3,3,3-Tetrafluoroprop-1-ene

<b>Toxicological effects</b>	As supplied, the material does not present a health hazard.
<b><u>Acute toxicity - oral</u></b>	
<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b><u>Acute toxicity - dermal</u></b>	
<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b><u>Acute toxicity - inhalation</u></b>	
<b>Notes (inhalation LC<sub>50</sub>)</b>	LC <sub>50</sub> >207000 ppm, Inhalation, Rat
<b><u>Skin corrosion/irritation</u></b>	
<b>Animal data</b>	Dose: 0.4 mL, 4 hours, Rabbit Primary dermal irritation index: 0 Not irritating.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	No information available.
<b><u>Respiratory sensitization</u></b>	
<b>Respiratory sensitization</b>	Based on available data the classification criteria are not met.
<b><u>Skin sensitization</u></b>	
<b>Skin sensitization</b>	Based on available data the classification criteria are not met.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Gene mutation: Negative.
<b>Genotoxicity - in vivo</b>	Chromosome aberration: Negative.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Two-generation study - NOEL >20000 ppm, Inhalation, Rat P This substance has no evidence of toxicity to reproduction.
<b>Reproductive toxicity - development</b>	Developmental toxicity: - NOAEC: 15000 ppm, Inhalation, Rat This substance has no evidence of toxicity to reproduction.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Based on available data the classification criteria are not met.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Not relevant.
<b>Inhalation</b>	Vapors may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

<b>Ingestion</b>	May cause discomfort if swallowed.
<b>Skin Contact</b>	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<b>Eye contact</b>	May cause temporary eye irritation. May cause temporary eye irritation.

### 12. Ecological information

### 13. Disposal considerations

#### Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**Air transport notes** Passenger Aircraft/Rail <75 kg. Cargo Aircraft Only <150 kg

#### UN Number

**UN No. (International)** UN1950

**UN No. (TDG)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (DOT)** 1950

#### UN proper shipping name

**Proper shipping name (TDG)** AEROSOLS, NON-FLAMMABLE 2.2, LTD QTY


**Proper shipping name (IMDG)** AEROSOLS, NON-FLAMMABLE 2.2, LTD QTY

**Proper shipping name (ICAO)** AEROSOLS, NON-FLAMMABLE 2.2, LTD QTY

**Proper shipping name (DOT)** AEROSOLS, NON-FLAMMABLE 2.2, LTD QTY

#### Transport hazard class(es)

#### Transport labels



#### Packing group

**Packing group (International)** Not applicable.

### 15. Regulatory information

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

**Guidance** CHIP for everyone HSG228.  
Workplace Exposure Limits EH40.  
Safety Data Sheets for Substances and Preparations.  
Approved Classification and Labelling Guide (Sixth edition) L131.

#### US Federal Regulations



## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

### CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

### SARA 313 Emission Reporting

The following ingredients are listed or exempt:

### SARA (311/312) Hazard Categories

Hazard

### US State Regulations

#### California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

#### Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

#### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

#### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

### Inventories

#### Canada - DSL/NDSL

The following ingredients are listed or exempt:

#### US - TSCA

Present.

### 16. Other information

<b>Revision date</b>	5/13/2020
<b>Revision</b>	16
<b>Supersedes date</b>	2/6/2020
<b>SDS No.</b>	23307
<b>Hazard statements in full</b>	H280 Contains gas under pressure; may explode if heated.
<b>ACA HMIS Health rating.</b>	Slight hazard. (1)
<b>ACA HMIS Flammability rating.</b>	Extremely flammable. (4)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B

### DIRECTIONS FOR USE

### PRODUCT LOGO

## Tensorgrip G67 Water Based Pressure Sensitive Flooring Adhesive Aerosol Can

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.