




F40

FAST DRY PRESSURE SENSITIVE ADHESIVE

DATA SHEET

TensorGrip



As part of our **FOAM & FABRIC** range, **F40** is a web spray adhesive designed for use in Domestic Furniture, Mattress and Office Furniture applications using the substrates listed.

PRODUCT DESCRIPTION

TensorGrip F40 is an well rounded, capable adhesive. Its aggressive and fast-drying pressure sensitive properties make it ideal for bonding a vast range of porous substrates while still maintaining tackiness and the ability to bond to polystyrene.

ADVANTAGES

- Very fast drying
- Long lasting high tack (pressure sensitive)
- Moisture and weather-resistant bond
- Non-chlorinated
- Will not attack polystyrene
- Full strength achieved in 24 hours
- 155°F (68°C) temperature resistant
- No chlorinated solvents
- No ODS (ozone depleting substances)

DIRECTIONS FOR USE

- **TensorGrip F40** is designed as a portable, self-contained spray system for field or shop applications.
- Apply adhesive to both surfaces to be mated, at 80% to 100% coverage.
- Allow enough time (2-4 minutes or until dry to the touch) for the adhesive to become tacky before bonding.
- Parts should be mated with as much pressure as practical.
- Normal coverage required with web spray pattern is approximately 80%; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately, although ultimate strength is achieved in 1-3 days.
- Canister system will spray adequately above 60° F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.

QUIN GLOBAL US

5710 F ST. Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quin-global.com

QUIN
GLOBAL

TensorGrip

F40

FAST DRY PRESSURE SENSITIVE ADHESIVE

DATA SHEET Tensorgrip

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

- Total Solids 26-32%
- VOC Content 542 g/L
- Color Red, Clear, Green, Blue; Aerosols Green Only
- System Flammability Flammable Adhesive; Flammable Propellant
- Solvent System Flammable
- Dry time 2-4 mins dependent on temp & humidity
- Open time Long
- Shelf Life 18 months from date of manufacture

PACKAGING

- 7L Disposable Canister
- 22L Disposable Canister
- 108L Returnable Canister
- 216L Returnable Canister

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.

QUIN GLOBAL US

5710 F ST, Omaha NE 68117

PH: +1 402 731 3636 | info.us@quin-global.com | www.quinglobal.com

QUIN
GLOBAL

Tensorgrip