TC42 SUPER HS INFUSION RTM ADHESIVE













As part of our COMPOSITES range, TensorGrip TC42 is an infusion molding adhesive designed for use in applications using the substrates listed.

PRODUCT DESCRIPTION

TensorGrip® TC42 is a high performance, solvent-based polymer adhesive, specifically designed to hold reinforcing fibers in place during the infusion process.

ADVANTAGES

- Used for Infusion/Vacuum Forming composites.
- Safely fuses laminating materials to structural core surfaces.
- Provides superior holding during forming process.
- Allows resin to obtain maximum tensile shear strength.

DIRECTIONS FOR USE

- TensorGrip® TC42 is designed as a portable, selfcontained spray system.
- Make sure surface is clean, dry and free of grease, oil, dirt and other contamination.
- Apply a sparing coat of TensorGrip TC42 to the surface to be bonded.
- Do not wet the surface.
- Allow to dry and become slightly tacky.
- Apply fiberglass materials. Fiberglass material should hold in place.
- Build up composite material and allow to cure normally (preferably overnight).
- Continue with vacuum infusion process; the adhesive will aid the flow of resin through the materials and will become part of the composite.
- Remove the composite from the mold.
- Recommended operating temperatures range from 60°F to 100°F. Canister system should be kept in warm area. In the event that the canister gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.
- Notice!!! Do not store at temperatures over 120° F.

CANISTER STORAGE/CHANGE OVER

- If you choose to leave the hose and spray gun on the canister, leave the valve on the canister open. Do not disconnect the hose/gun from the canister. Close and lock the spray gun.
- To change or disconnect canister: turn canister valve to the off position, spray out remaining adhesive left in the hose, disconnect the spray hose and gun from the canister.
- Reconnect the spray hose to a new canister of adhesive. OR if you are NOT connecting to a new canister, connect hose to canister of cleaning solvent (sold separately) and spray out until liquid is clear which indicates that the hose and gun is clean.







TC42 SUPER HS INFUSION RTM ADHESIVE



CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

Total Solids 26-32%
VOC Content 180g/L
Color Clear Red

System Flammability Flammable adhesive; Non-Flammable propellant

Solvent System Methyl Acetate & Hexane

Dry time 2-4 mins dependent on temp & humidity

Open time 5-20 minutes

Shelf Life 18 months from date of manufacture

PACKAGING

650ml Aerosol Cans22L Disposable Canister

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.



