SAFETY DATA SHEET TensorGrip TC43 SuperWeb Infusion Spray Adhesve

1. Identification

Product identifier

Product name TensorGrip TC43 SuperWeb Infusion Spray Adhesve

Product number USA

Recommended use of the chemical and restrictions on use

Application Canister Spray Adhesive

Details of the supplier of the safety data sheet

Supplier

Quin Global 5710 F St (402) 731 3636 (402) 731 1473

marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Gas 2 - H221 Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H335, H336

Environmental hazards Aquatic Chronic 2 - H411

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram









Signal word

Danger

Hazard statements H221 Flammable gas.

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P261 Avoid breathing vapor/ spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/ doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

AT(d) 31.4% of the mixture consists of ingredient(s) of unknown acute dermal toxicity. AT(o) 31.4% of the mixture consists of ingredient(s) of unknown acute oral toxicity.

Contains Dimethyl Ether, Pentane, Acetone

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Dimethyl Ether 30-60%

CAS number: 115-10-6

Classification

Flam. Gas 1 - H220

Press. Gas, Liquefied - H280

Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2B - H320 STOT SE 3 - H335, H336

Pentane 30-60%

CAS number: 78-78-4 M factor (Acute) = 1

Classification

Flam. Liq. 1 - H224 Eye Irrit. 2A - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

Acetone 1-5%

CAS number: 67-64-1

Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2A - H319

STOT SE 3 - H336

Revision date: 2/24/2017 Revision: 1 Supersedes date: 2/18/2016

TensorGrip TC43 SuperWeb Infusion Spray Adhesve

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Remove affected person from source of contamination. Place unconscious person on their

side in the recovery position and ensure breathing can take place. Get medical attention if any

discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Get medical attention immediately. Never give anything by mouth to an unconscious person.

Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a

position comfortable for breathing.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the

person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get

medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

Inhalation May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The liquid is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

Eye contact Causes serious eye irritation. Burns can occur. A single exposure may cause the following

adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged

contact causes serious eye and tissue damage.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers

can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source

of ignition and flash back.

Advice for firefighters

Revision date: 2/24/2017 Revision: 1 Supersedes date: 2/18/2016

TensorGrip TC43 SuperWeb Infusion Spray Adhesve

for firefighters

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of

ignition near spillage.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and

place into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide

> adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the

ground.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container. Pressurized container: Must not be exposed to temperatures above

50°C/120°F

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Dimethyl Ether

Long-term exposure limit (8-hour TWA): WEEL:US.AIHA = Workplace Environmental Exposure Level Guides 1000 ppm

Long-term exposure limit (8-hour TWA): ACGIH 600 ppm

Acetone

Long-term exposure limit (8-hour TWA): ACGIH 500 ppm Short-term exposure limit (15-minute): ACGIH 750 ppm

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m³

Ceiling exposure limit: NIOSH: National Institute of Occupational Safety and Health 250 ppm 590 mg/m³ vapour

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen. OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment





Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

Eye/face protection Wear chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level

exposures, a supplied air respirator should be used.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Aerosol.

Color Clear. Red.

Odor Organic solvents.

Initial boiling point and range Not determined.

Flash point -41°C/-42°F Not specified.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 3.4 g/100 g Upper flammable/explosive limit: 18 g/100 g

Vapor pressure Not determined.

Vapor density Not determined.

Relative density .7087

Solubility(ies) Negligibly soluble in water

Volatile organic compound This product contains a maximum VOC content of 552.55 g/l.

10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

Revision date: 2/24/2017 Revision: 1 Supersedes date: 2/18/2016

TensorGrip TC43 SuperWeb Infusion Spray Adhesve

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Oxidizing agents. Reducing agents.

Hazardous decomposition

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

products Hydrogen chloride (HCl). Hydrocarbons. Aldehydes.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 7,622.22

Acute toxicity - dermal

ATE dermal (mg/kg) 16,768.89

Acute toxicity - inhalation

ATE inhalation (gases ppm) 9,000.0
ATE inhalation (vapours mg/l) 244.44

Dimethyl Ether

Acute toxicity - inhalation

Acute toxicity inhalation

308.5

(LC₅o gases ppmV)

Species Rat

ATE inhalation (gases

4,500.0

ppm)

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation. Central nervous system depression. Skin and eye

irritation.

Aspiration hazard

Aspiration hazard No data available.

Medical Symptoms Central nervous system depression. Frostbite. Respiratory system irritation. Skin

irritation. Eye irritation.

Pentane

Acute toxicity - oral

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 vapours mg/l)

1,280.0

Revision date: 2/24/2017 Revision: 1 Supersedes date: 2/18/2016

TensorGrip TC43 SuperWeb Infusion Spray Adhesve

Species Rat

ATE inhalation (vapours

mg/l)

Serious eye damage/irritation

Serious eye Irritation of eyes is assumed.

11.0

damage/irritation

Germ cell mutagenicity

Genotoxicity - in vitro Ames Test Results: Negative.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

General information Absorbtion of large quantities may cause: Dizziness. Euphoria. Agitation.

Convulsions. Narcosis.

Acetone

Acute toxicity - oral

Acute toxicity oral (LD₅o 5,800.0

mg/kg)

Species Rat

500.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 20,000.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation

76.0

(LC₅₀ dust/mist mg/l)

Species Rat

ATE inhalation (vapours 11.0

mg/l)

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness

Inhalation Mucosal irritations. Absorption. Revision date: 2/24/2017 Revision: 1 Supersedes date: 2/18/2016

TensorGrip TC43 SuperWeb Infusion Spray Adhesve

Ingestion Irritating. May cause nausea, stomach pain and vomiting. Aspiration hazard if

swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Skin Contact This product is moderately irritating. May be absorbed through the skin. Repeated

exposure may cause skin dryness or cracking.

Eye contact This product is strongly irritating. Risk of corneal clouding.

Route of entry Inhalation Skin and/or eye contact

Target Organs Eyes

12. Ecological Information

13. Disposal considerations

Waste treatment methods

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

Air transport notes Cargo aircraft only. <75kg

UN Number

UN No. (TDG) 3501

UN No. (ICAO) 3501

UN No. (DOT) 3501

UN proper shipping name

Proper shipping name (TDG) Chemical Under Pressure, Flammable, N.O.S.

Proper shipping name (DOT) Chemical Under Pressure, Flammable, N.O.S.

Transport hazard class(es)

TDG class 2

TDG label(s) 2.1

Transport labels



Packing group

Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

The following ingredients are listed or exempt:

Pentane

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Acetone

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Pentane

SARA (311/312) Hazard Categories

Present.

Dimethyl Ether

Acute

Health hazard

Pressure

Fire

Hazard

Pentane

All the ingredients are listed or exempt.

Acetone

Acute

Chronic

Health hazard

Fire

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Ths product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

Massachusetts "Right To Know" List

Present.

Dimethyl Ether

Pentane

Acetone

Rhode Island "Right To Know" List

Acetone

Present.

Minnesota "Right To Know" List

Present.

Dimethyl Ether

Acetone

New Jersey "Right To Know" List

Present.

Dimethyl Ether

Acetone

Pennsylvania "Right To Know" List

Present.

Dimethyl Ether

Pentane

Acetone

Inventories

Canada - DSL/NDSL

DSL

Dimethyl Ether

Pentane

Acetone

US - TSCA

Present.

Dimethyl Ether

Pentane

Acetone

16. Other information

Revision date 2/24/2017

Revision

 Supersedes date
 2/18/2016

 SDS No.
 21970

Hazard statements in full

H220 Extremely flammable gas.

H221 Flammable gas.

H222 Extremely flammable aerosol.

H224 Extremely flammable liquid and vapor. H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H320 Causes eye irritation. H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

ACA HMIS Health rating. Moderate hazard. (2)

ACA HMIS Flammability

rating.

Ignites easily. (3)

ACA HMIS Physical hazard

rating.

Normally stable. (0)

ACA HMIS Personal protection rating.

В

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application